


# Open-Q<sup>™</sup> 2200 Series SIP

Based on Qualcomm® QCS2290 & QRB2210 Processors





# Open-Q<sup>™</sup> 2200 Series

The Open-Q 2200 Series SIP is an entry-tier solution based on the Qualcomm® QCS2290 (Android) & QRB2210 (Yocto Linux) processors, with on-board audio codec, 2GB of LPPDR4 memory, 16GB of eMMC, and pre-certified Wi-Fi and Bluetooth. It is an entry-tier solution that delivers greater performance, graphics, camera capabilities, and improved power performance compared to previous generations. It is a 35 x 35mm LGA package that is ideal for industrial IoT applications such as handhelds, panels, POS/kiosks, vending machines, exercise equipment, and camera applications..

Along with the companion development kit, OS and SDKs, and available accessories, it will accelerate your time to market for innovative new products requiring advanced imaging and computer vision performance in low-cost and low-power embedded situations.

## **Customer Benefits**

- Entry-tier solution that delivers greater performance, graphic, camera capabilities, and improved power performance.
- Scalable volume deployment through future ConsoleFlow™ support for device management, zero-touch provisioning and OTA updates of functionality and security
- · Secure compute platform
- · Long device life cycle

#### **Target Markets**

- Industrial IoT applications including handhelds and panels
- · Camera applications
- POS/kiosk, vending machines, exercise equipment displays
- Entry-level robotics including warehouse and logistics

## **Engineering Services:**

We provide a full solution – our unparalleled engineering expertise and product development skills deliver innovative products that are cost-effective and can jumpstart your go-to-market timeline.

Our business model offers turnkey product development services, or we can augment your team in specific areas of development. The choice is yours.

### Key development expertise in:

- · Camera development and tuning
- · Voice control
- Machine learning
- · Mechanical & RF design
- Thermal & power optimization

IoT product development made easy.

Qualcomm





## Hardware Specifications:

| Product Name          | Open-Q 2200 Series SIP   |  |
|-----------------------|--|--|
| Processor             | 4-Core, 64-bit ARM Cortex A53, up to 2.0GHz  |  |
| Memory                | 2GB LPDDR4   |  |
| Storage               | 16GB eMMC  |  |
| External Storage      | uSD  |  |
| Wi-Fi / BT            | 802.11 a/b/g/n/ac, 1x1; BT 5.0 with WCN3950  |  |
| Location              | <ul> <li>Support with external GNSS circuitry and WGR7640. Please contact us for more details.</li> <li>Gen 9, GPS, Glonass, BeiDou, Galileo, QZSS, and SBAS.</li> <li>NavIC support with WGR7640</li> </ul> |  |
| Modem                 | No   |  |
| Display Interfaces    | <ul> <li>One 4-lane; DSI D-PHY 1.2. Split link supported</li> <li>Adreno™ 702 at 845 MHz</li> <li>OpenGL ES 3.1, Vulkan 1.1, OpenCL 2.0</li> <li>HD+ (1680x720) @ 60 fps</li> </ul>                          |  |
| Camera Interfaces     | 2-ISP     Two cameras: 13 MP +13 MP @ 30fps     One camera: 25MP @ 30fps   |  |
| Video capabilities    | 1080p 30 fps encode / 1080p 30fps decode   |  |
| Audio                 | 4 x DMIC, support for two voice activation engines, integrated low power island for voice activation, supports always-on noise suppression   |  |
| 1/0                   | USB 3.1 Type C, SDIO, UART, SPI, I2C, I3C, GPIO  |  |
| PCle                  | None   |  |
| Battery Charger       | Yes  |  |
| Operating Temperature | Extended (-25°C to 85°C)   |  |
| Form Factor           | SIP (LGA)  |  |
| Dimensions            | 35 x 35 x 2.8mm  |  |
| Certification         | FCC, RED   |  |
| Software:             |  |  |

## Software:

# **Development Kits**



The Open-Q™ 2200 SIP is compatible with the Open-Q AL or RB development kits.

# Purchasing Information:

| SKU             | Description                                  | Software                   |
|-----------------|--|----------------------------|
| QC-SIP-2290CS-A | Open-Q 2290CS SIP, 2GB LPDDR4, 16G eMMC v5.1 | Android™ 12 Go             |
| QC-SIP-2210RB-A | Open-Q 2210RB SIP, 2GB LPDDR4, 16G eMMC v5.1 | Yocto Linux (Dunfell, 5.4) |

Alternate SIP configurations available by special order (minimum order quantities apply) - For example, different memory size, etc. Contact sales to discuss your specific needs today.

#### Certifications \_









# Contact Information:

## **Americas**

americas\_sales@lantronix.com www.lantronix.com NASDAQ: LTRX

#### Asia/Pacific

asiapacific\_sales@lantronix.com





#### **Europe**

eu\_sales@lantronix.com

© 2023 Lantronix, Inc. All rights reserved. Lantronix is a registered trademark of Lantronix, Inc. in the U.S. and other countries. Open-Q and ConsoleFlow are trademarks of Lantronix, Inc. Qualcomm QCS2290, Qualcomm QCS2210, and Qualcomm Adreno are products of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm and Adreno are trademarks of Qualcomm Incorporated, registered in the United States and other countries. Android is a trademark of Google LLC. All other trademarks are the property of their respective owners. Specifications subject to change without notice. Not all features listed may be supported in software. Open-Q 2200 Series SIP MPB-00160 Rev B

