


Open-Q™ 4290 SIP

Based on Qualcomm® QCS4290 System-On-Chip



Open-Q™ 4290CS

The Open-Q™ 4290 SIP is a cost-effective solution that delivers powerful performance, vivid graphics, dynamic camera capabilities, and a broad range of connectivity options.

Designed for advanced AI vision applications, the QCS4290 chipset utilizes Qualcomm Technologies' heterogenous compute expertise to provide an SoC with multiple specialized processing cores.

This is a Wi-Fi 5 solution with some Wi-Fi 6 features: TWT & 8SS. With security, advanced camera features, and high-speed interfaces, the Open-Q 4200 SIP creates the perfect computing core for a variety of edge AI video analytic applications.

Along with the companion development kit, OS and SDKs, and available accessories, it will accelerate your time to market for innovative new products requiring advanced imaging and computer vision performance in low-cost and low-power embedded situations.

Key Features

- Compact SIP with Qualcomm QCS4290 SoC, 8-core 2.0/1.8 GHz processor
- 3rd generation Qualcomm AI Engine
- Vivid graphics with Qualcomm Adreno 610 GPU
- Multiple high speed connectivity options
- Up to 6GB LPDDR4 and 256GB eMMC
- Long term support with extended life hardware and software support through 2027

Applications/Markets

- Intelligent surveillance camera, dash camera, body camera
- Fleet management with video analytics
- Warehouse and logistic robots
- Rugged handheld computer
- Interactive display boards
- Drone

Engineering Services:

We provide a full solution – our unparalleled engineering expertise and product development skills deliver innovative products that are cost-effective and can jumpstart your go-to-market timeline.

Our business model offers turnkey product development services, or we can augment your team in specific areas of development. The choice is yours.

Key development expertise in:

- Camera development and tuning
- Voice control
- Machine learning
- Mechanical & RF design
- Thermal & power optimization

IoT product development made easy.



Hardware Specifications:

Processors	8-core 2.0/1.8 GHz processor + 1GHz cDSP
Memory/Storage	2GB – 6GB LPDDR4 16GB – 256GB eMMC SD 3.0
Wireless	802.11 a/b/g/n/ac, Wi-Fi 6-ready 8x8 sounding & Target Wake Time (TWT), 1x1 MU-MIMO 2.4/5 GHz, WPA3, Bluetooth 5.1, and FM RDS/RBDS
Camera Interfaces	Three 4-lane CSIs (4/4/4 or 4/4/2/1)
Video Performance	Encode & Decode: Up to 1080p 60fps encode / 1080p 60fps decode Decode: Up to 1080p60 8-bit H.264, 1080p60 8-bit HEVC (H.265), VP9 Encode: Up to 1080p60 8-bit HEVC (H.265), 1080p60 8-bit H.264
Video Interface	One 4-lane MIPI DSI Display interfaces, supporting D-PHY 1.2 (1.5 Gbps / lane)
Audio	4x DMIC interfaces, 3x analog mic inputs, headphone, line-out, and speaker outputs
Power/Battery	Battery charging solution to be designed on customer board
I/O	4-bit SD 3.0, USB 3.1 Type-C, UART, I2C, I3C, SPI, configurable GPIOs
GNSS	Single-frequency, multi-constellation GNSS functionality with external WGR7640 RF receiver
Operating Environment	-20 to +85°C
Form Factor	36mm x 36mm x 2.76mm LGA package
Certification	FCC, RED

Software:

Open-Q 4290CS SIP	Android™ 12, Android 12 Go
--------------------------	----------------------------

Development Kits



The Open-Q SIP family is compatible with Open-Q AL2 development kit.

Purchasing Information:

SKU	Description	Software
QC-SIP-4290CS-A	Open-Q 4290CS SIP, 2GB LPDDR4, 16G eMMC, Wi-Fi, BT	Android 12 Go
QC-SIP-4290CS-B	Open-Q 4290CS SIP, 4GB LPDDR4, 64GB eMMC, Wi-Fi, BT	Android 12
QC-SIP-4290CS-C	Open-Q 4290CS SIP, 4GB LPDDR4, 256GB eMMC, Wi-Fi, BT	Android 12

Alternate SIP configurations available by special order (minimum order quantities apply) - For example, different memory size, etc. Contact sales to discuss your specific needs today.

Certifications



Contact Information:

Americas

americas_sales@lantronix.com
www.lantronix.com
NASDAQ: LTRX

Asia/Pacific

asiapacific_sales@lantronix.com

Europe

eu_sales@lantronix.com