


Open-Q[™] **865XR SOM** (System on Module)

Based on the Qualcomm[®] Dragonwing[™] SXR2130P processor







Horsepower at the Edge

- The 865XR SOM offers the perfect computing core for a variety of leading edge IoT applications
- The ideal solution to accelerate your "time to revenue" on product development
- The Qualcomm[®] Al Engine provides 2x the performance of the previous generation with up to 15 TOPS

The Open-Q™ 865XR SOM is an ultra-compact (50mm x 29mm) production-ready, pre-certified SOM based on the powerful Qualcomm SXR2130P SoC. The 865XR utilizes Qualcomm® Technologies' heterogenous compute expertise to offer a System-on-Chip with multiple specialized processing cores:

- 5th generation Qualcomm® AI Engine
- Qualcomm Spectra™ ISP, Qualcomm® Adreno™ GPU, and Qualcomm® Hexagon™ DSP
- · Power, processing and professional quality imaging
- Coupled with the latest Wi-Fi 6 connectivity, advanced camera features, and many highspeed interfaces

Key Features

- Qualcomm Dragonwing™ SXR2130P processor
- 6GB LPDDR5 RAM + 64GB UFS 3.1 Flash
- 3x MIPI CSI camera ports
- · 2x MIPI DSI display ports
- 1x 2-lane PCIe Gen3 interface
- USB Type-C with DisplayPort v1.4
- · Pre-certified Wi-Fi and Bluetooth
- Wi-Fi 6 802.11ax 2x2 MU-MIMO Wi-Fi / BT 5.1

Applications

- Al box—multi-stream encode/decode/ Al processing
- Video conference systems
- · Multi-camera systems
- · Machine vision platforms
- · Advanced high resolution multi-display systems
- Medical imaging
- · Handheld data collectors

Engineering Services:

We provide a full solution – our unparalleled engineering expertise and product development skills deliver innovative products that are cost-effective and can jumpstart your go-to-market timeline.

Our business model offers turnkey product development services, or we can augment your team in specific areas of development. The choice is yours.

Key development expertise in:

- Camera development and tuning
- · Voice control
- Machine learning
- Mechanical & RF design
- Thermal & power optimization

IoT product development made easy.









Hardware Specifications:

• Processors	Qualcomm® Dragonwing™ SXR2130P SoC built on 7nm technology: Kryo™ 585 Octa-core CPU: 1Kryo Gold prime @ 2.84 GHz + 3 Kryo Gold @ 2.42 GHz + 4 Kryo Silver @ 1.81 GHz Hexagon DSP with quad Hexagon Vector eXtensions		
	Adreno 650 GPU @ Fmax = 587 MHz Qualcomm Spectra 480 Image Signal Processor Adreno 665 Video Processing unit	Adreno 995 Display Processing unit NPU230 Neural Processing unit SPU240 Secure Processing unit	
Memory/Storage	6GB or 8GB LPDDR5 RAM @ 2750MHz, 64GB UFS 2.1 or 128GB UFS 3.0		
• Wireless	Pre-certified for FCC, ISED (Canada), RED (EU) 802.11ax 2x2 MU-MIMO + Bluetooth 5.1, Bluetooth Milan ready		
Display Interfaces	Up to three 4K displays (1 internal display through DSI and 2 external displays through DisplayPort) 2x 4-lane MIPI DSI D-PHY 1.2, up to 5040 × 2160 @ 60 fps (or 120 Hz in VR mode) + touchscreen support DisplayPort v1.4 on USB Type-C, at 8.1 Gbps/lane, with USB3 and USB2 data concurrency		
Camera Interfaces	3x 4-lane MIPI CSI camera ports + CCI I2C control	Qualcomm Spectra 480 ISP supporting multiple concurrent cameras 64 MP 30 fps ZSL with a dual ISP	
Video Performance	Video decode up to 4K240/8K60 Video encode up to 4K120/8K30	Concurrent 4K60 decode & 4K30 encode for wireless display	
• Audio	Supports WCD938x high fidelity audio codec and WSA881x speaker amp on carrier board Dedicated Hexagon audio DSP SoundWire, MI2S, DMIC, TDM/PCM interfaces for audio devices on carrier board		
• High Speed Connectivity	1x PCle Gen3 2-lane 1x USB 3.1 with support for Type-C + DisplayPort v1.4 with USB SS data concurrency 1x USB 3.1 Type-A		
• I/O Interfaces	4-bit SD 3.0, UART, I2C, I3C, SPI, configurable GPIOs, sensor I/O to dedicated Hexagon sensor DSP		
• Power/Battery	Power management and battery charging solution on SOM		
Operating Environment	Input voltage: 3.7V nominal Operating Temperature: -25°C to +85°C Tc (component case temperature)		
Form Factor	50mm x 29mm with 2x 100-pin + 1x 120-pin board to board connectors		
Software:	1		
OS Support	Android™ 10 — Note that all hardware features may not be supported by SW		



Companion Development Kit available separately

Purchasing Information:

• Open-Q™ 865XR SOM (6+64GB)	PN: QC-DB-U10004
• Open-Q™ 865XR SOM (8+128GB)	PN: QC-DB-U10004A

Alternate SOM configurations available by special order (minimum order quantities apply) e.g. different memory size, etc. Contact sales to discuss your specific needs today.

Certifications







© 2025 Lantronix, Inc. All rights reserved. Lantronix is a registered trademark of Lantronix, Inc. in the U.S. and other countries. Open-Q is a trademark of Lantronix, Inc. Qualcomm branded products are products of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm and Qualcomm Dragonwing are trademarks or registered trademarks of Qualcomm Incorporated. Qualcomm Dragonwing SXR2130P, Qualcomm Adreno, Qualcomm Hexagon, Qualcomm Kyo, Qualcomm Spectra and Qualcomm All Engine are products of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm, Adreno, Evo and Spectra are trademarks of Qualcomm Incorporated, registered in the United States and other countries. All other trademarks are the property of their respective owners. Specifications subject to change without notice. Not all features listed may be supported in software. MPB-00110 Rev C (A4)

Learn more at lantronix.com/open-q-865xr-som

