LANTRONIX®
Formerly Transition Networks

TN-GLC-T Series

Cisco Compatible Gigabit SFP Modules

1000Base-T (RJ-45)



TN-GLC-T-MG

Specifications

Standards	IEEE 802.3
Dimensions	Width: 0.95" [24 mm] Depth: 2.8" [71 mm] Height: 0.54" [14 mm]
Power Consumption	1.0 Watts
Power Input	3.3V
Environment	Operating: 0°C to +70°C Storage: -40°C to +85°C
Certifications	IEC-60825, FDA 21, CFR 1040.10 and 1040.11, UL Listed
Warranty	Lifetime

Ordering Information

TN-GLC-T
1000Base-T (RJ-45) [100 m/328 ft.]

TN-GLC-T-PK
Pack of (20) TN-GLC-T Modules

TN-GLC-T-MG
10/100/1000Base-T (RJ-45) [100 m/328 ft.]

NOTE: The Lantronix TN-GLC-T series small form factor pluggable (SFP) transceiver modules are designed to install in any SFP port allowing for 1000Base-T interfaces to the network through the SFP connector. The TN-GLC-T transceivers are Cisco Compliant* and are designed for bi-directional serial-optical data communication such as Gigabit Ethernet or fiber channel at speeds up to 1.25 Gbps.

*Lantronix SFP modules fully comply with the Multi-Sourcing Agreement (MSA). This compliance allows our SFP modules to be used in all other MSA compliant SFP platforms. In addition, Lantronix SFP modules are also Compliant with all Cisco SFP-based routers and switches, as well as Cisco's IOS software. Lantronix SFP modules ARE NOT Cisco OEM brand modules.

© 2026 Lantronix, Inc. All rights reserved. Lantronix is a registered trademark of Lantronix, Inc. in the U.S. and other countries. All other trademarks are the property of their respective owners. Specifications subject to change without notice. Not all features listed may be supported in software. MPB-00354 Rev A

Learn more at lantronix.com/tn-glc-t-series