

Product Line Card



SI-IES-5x1D-LRT Series



SESPM Series



SISPM1040-582-LRT



SM48TAT4XA-RP



SM24TBT4XPA



SMTATSA Series

Product	Access/PoE						Uplink		General		
Product Part Number ¹	Access/ PoE Ports	Access Data Rate	PoE+ or PoE++	PoE Budget (Watts)	Power Supply Included	Redundant Power	Uplink Ports	Uplink Data Rate	Commercial/ Hardened ²	Managed/ Unmanaged	Mount
M/GE-PSW-PSE-01-xx	1	1 GbE	PoE+	30	Yes	No	1	1G SFP	Commercial	Unmanaged	Wall/Desk/DIN Rail
SGPAT1040-105-xx	1	1 GbE	PoE+	30	Yes	No	1	1G SFP	Commercial	Unmanaged	Wall/Desk/DIN Rail
SGPAT1040-205-xx	1	1 GbE	PoE+	30	Yes	No	2	1G SFP	Commercial	Unmanaged	Wall/Desk/DIN Rail
SGPAT1040-305-xx	2	1 GbE	PoE+	60	Yes	No	2	1G SFP	Commercial	Unmanaged	Wall/Desk/DIN Rail
E02Px4052-111	1	1 GbE	PoE+	30	No	No	1	1G SFP/RJ45 Combo	Extended	Managed	Wall/Desk/DIN Rail
E0CPx4020-110	1	1 GbE	PoE+	30	No	No	1	1G SFP/RJ45 Combo	Extended	Managed	Wall/Desk/DIN Rail
SI-IES-5200-LRT	1	up to 10GE	PoE++	90	No	Yes	1	up to 10GE RJ45	Hardened	Unmanaged	Wall/DIN
SI-IES-511D-LRT	1	1/2.5 GbE	PoE++	90	No	Yes	1	1G/10G SFP/SFP+	Hardened	Unmanaged	Wall/DIN Rail
SI-IES-521D-LRT	2	1/2.5 GbE	PoE++	180	No	Yes	1	1G/10G SFP/SFP+	Hardened	Unmanaged	Wall/DIN Rail
SM48TAT4XA-RP-xx	48	1 GbE	PoE+	780	Yes	Yes	4	1G/10G SFP/SFP+	Commercial	Managed	Rack/Wall/Desk
SM24TAT4XB-xx	24	1 GbE	PoE+	360	Yes	No	4	1G/10G SFP/SFP+	Commercial	Managed	Rack/Wall/Desk
SISPM1040-384-LRT-C	8	1 GbE	PoE+	240	No	Yes	4	1G SFP	Hardened	Managed	DIN Rail
SISPM1040-3248-L3	24	1 GbE	PoE+	360	No	Yes	4	1G/10G SFP/SFP+	Hardened	Managed	Rack/Wall/Desk
SM8TAT2SA-xx	8	1 GbE	PoE+	120	Yes	No	2	1G SFP	Commercial	Managed	Rack/Wall/Desk
SM16TAT2SA-xx	16	1 GbE	PoE+	240	Yes	No	2	1G SFP	Commercial	Managed	Rack/Wall/Desk
SM24TAT2SA-xx	24	1 GbE	PoE+	360	Yes	No	2	1G SFP	Commercial	Managed	Rack/Wall/Desk

¹ Power Cord Included. To order the corresponding country specific power cord, add the extension to the end of the part number; -NA, -LA, -EU, -UK, -SA, -JP, -AZ, -BR

² Commercial = 0° to +50° C, Hardened = -40° to +75° C operating temperature, Extended = 0° to +65° C

Product Line Card



SI-IES-5x1D-LRT Series



SESPM Series



SISPM1040-582-LRT



SM48TAT4XA-RP



SM24TBT4XPA



SMTATSA Series

Product	Access/PoE						Uplink		General		
Product Part Number ¹	Access/ PoE Ports	Access Data Rate	PoE+ or PoE++	PoE Budget (Watts)	Power Supply Included	Redundant Power	Uplink Ports	Uplink Data Rate	Commercial/ Hardened ²	Managed/ Unmanaged	Mount
SISTP1040-342-LRT	4	1 GbE	PoE+	120	No	Yes	2	1G SFP	Hardened	Unmanaged	DIN Rail
SISPM1040-362-LRT	4	1 GbE	PoE+	120	No	Yes	2	1G SFP	Hardened	Managed	DIN Rail
SISTP1040-382-LRT	8	1 GbE	PoE+	240	No	Yes	2	1G SFP	Hardened	Unmanaged	DIN Rail
SISTP1040-382B-LRT	8	1 GbE	PoE+	60/120	No	Yes	2	1G SFP	Hardened	Unmanaged	DIN Rail
SISPM1040-3166-L3	16	1 GbE	PoE+	240	No	Yes	2	1G/10G SFP/SFP+	Hardened	Managed	Rack/Wall/Desk
SM24TBT4SA-xx	24	1 GbE	PoE++	740	Yes	No	4	1G SFP/RJ45 Combo	Commercial	Managed	Rack/Wall/Desk
SM8TBT2SA-xx	8	1 GbE	PoE++	240	Yes	No	2	1G SFP/RJ45 Combo	Commercial	Managed	Rack/Wall/Desk
SESPM1040-541-LT-DC	4	1 GbE	PoE++	240	Yes	Yes	2	1G SFP/RJ45 Combo	Hardened	Managed	IP66 Pole/Wall
SESPM1040-541-LT-AC-xx	4	1 GbE	PoE++	180	Yes	Yes	2	1G SFP/RJ45 Combo	Hardened	Managed	IP66 Pole/Wall
SISPM1040-582-LRT	8	1 GbE	PoE++	480	No	Yes	2	1G SFP	Hardened	Managed	DIN Rail
SISTP1040-551-LRT	4	1 GbE	PoE++	360	No	Yes	1	1G SFP/RJ45 Combo	Hardened	Unmanaged	DIN Rail
SM24TBT4XPA-xx	24	1/2.5 GbE	PoE++	740	Yes	No	4	1G/10G SFP/SFP+	Commercial	Managed	Rack/Wall/Desk
SM24TBT2DPB-2XPS-xx	24	1 GbE	PoE++	2160	Yes	Yes	4	1G SFP/RJ45 Combo	Commercial	Managed	Rack/Wall/Desk
SM24TBT2DPB-920-xx	24	1 GbE	PoE++	900	Yes	Yes	3	1G SFP/RJ45 Combo	Commercial	Managed	Rack/Wall/Desk
SM24TBT2DPB-xx	24	1 GbE	PoE++	1080	Yes	Yes	2	1G SFP/RJ45 Combo	Commercial	Managed	Rack/Wall/Desk
LSS2200-8P	8	1 GbE	PoE++	720	No	Yes	2	1G/10G SFP/SFP+	Hardened	Managed	DIN Rail

¹ Power Cord Included. To order the corresponding country specific power cord, add the extension to the end of the part number; -NA, -LA, -EU, -UK, -SA, -JP, -AZ, -BR

² Commercial = 0° to +50° C, Hardened = -40° to +75° C operating temperature, Extended = 0° to +65° C