LANTRONIX®

NEW!

Open-Q™ 8550CS SOM

Based on Qualcomm® Dragonwing™ QCS8550 System-on-Chip



Ideal for Advanced Video and AI Applications

The Open-Q™ 8550CS offers a premium performance level of 48 INT8, 12 FP16 TOPs, meeting the higher AI/ML requirements for extreme edge computing, including Edge devices, Edge servers and Edge AI boxes. Based on Qualcomm's Dragonwing™ QCS8550, the Open-Q 8550CS offers several benefits: low power consumption with a 4nm process, maximum heterogeneous computing, an 8th-generation AI Engine delivering 10x performance over the previous generation, enterprise-level connectivity with Wi-Fi 7 supporting up to 5.8Gbps, and best-in-class performance across compute processing, camera, AI, security, and audio.

Lantronix offers TAA and NDAA compliant products with at least 10 years of longevity for the Open-Q 5430CS, Open-Q 6490CS, Open-Q 5165RB, Open-Q 8250CS, and Open-Q 8550CS with strict Bill-of-Material and quality control. Combined with over 20 years of hardware design and software development experience, and 1200+ successful projects, Lantronix will be your long-term partner, ensuring the ongoing success of your product journey.

BLUE UAS FRAMEWORK LISTED

DCMA-vetted, NDAA-compliant AI companion computer for drones. Build on a module already approved for Blue UAS and reduce your time to market.

BLUE UAS

Key Features

- Qualcomm® 8550 SoC
- Up to 16GB LPDDR5 RAM + 128GB UFS Flash
- Android™ 13 and Linux Yocto Kirkstone
- On-device AI Engine with Qualcomm Hexagon™ Tensor Processor (HTP)
- Dedicated Computer Vision Engine
- Multiple MIPI camera and display ports
- Multiple high speed connectivity options
- Blue UAS Framework listed

Applications

- Multi-camera and smart camera systems
- Edge AI gateways
- Video collaboration
- Retail
- Cloud Gaming
- Industrial drones
- Autonomous mobile robots

Engineering Services:

We provide a full solution – our unparalleled engineering expertise and product development skills deliver innovative products that are cost-effective and can jumpstart your Go-to-Market timeline.

Our business model offers turnkey product development services, or we can augment your team in specific areas of development. The choice is yours.

Key development expertise in:

- Camera development and tuning
- Voice control
- Machine learning
- Mechanical & RF design
- Thermal & power optimization

IoT product development made easy.

Qualcomm Dragonwing

PRODUCT LONGEVITY PROGRAM

LANTRONIX®

Lantronix Open-Q™ 8550CS SOM

Production Ready
Computing Module


Hardware Specifications:

• **Processors**		Qualcomm® 8550CS SoC built on 4nm technology: Kryo™ Octa-core CPU: 1 Prime @ 3.2 GHz + 4 Gold @ 2.8 GHz + 3 Silver @ 2.0 GHz	
		Adreno™ 740 GPU Spectra™ Image signal processor Adreno™ 8550 video processing unit	Adreno™ 1295 display processing unit Dual eNPU V3, 4x HVX, HMX, 48 INT8, 12 FP16 TOPs Secure processing unit
• **Memory/Storage**		8GB LPDDR5x @ 4200MHz, and 128GB UFS, or 16GB LPDDR5x @ 4200MHz and 128GB UFS	
• **Wireless**		Wi-Fi 7 802.11be 2x2 MU-MIMO + Bluetooth 5.3 capable	
• **Display Interfaces**		Up to four concurrent displays. Up to QHD+ @ 144Hz on-device display, up to 4K@60 Hz external display 2x 4-lane MIPI DSI D-PHY 1.2 Support DisplayPort v1.4 on USB Type-C with USB3.1 Gen 2	
• **Camera Interfaces**		8x MIPI CSI D-PHY 1.2 or C-PHY 2.0 camera ports + CCI I2C control	Up to five concurrent cameras, 18bpp, 64 + 36 MP30, or 3x 36 MP30, or 1x 108 MP 30 fps ZSL, 3IFE + 2 IFE Lite, Always-on camera
• **Video Performance**	Decode	Video decode up to 4K240/8K60. Native decode support for H.265 Main 10, H.265 Main, H.264 High, VP9 profile 2	
	Encode	Video encode up to 4K120/8K30. Native encode support for H.265 Main 10, H.265 Main, H.264 High	
	Dec & Enc	Concurrent 4K60 Dec and 4K60 Enc	
• **Audio**		Supports WCD938x high fidelity audio codec and WSA884x speaker amp on carrier board. Dedicated Hexagon™ audio DSP, SoundWire, MI2S, DMIC interfaces for audio devices on carrier board	
• **High Speed Connectivity**		2x PCIe Gen3 2-lane Support SGMII and USXGMII interfaces 1x USB 3.1 Gen 2 with support for Type-C + DisplayPort v1.4 1x USB 3.1 Gen 1	
• **I/O Interfaces**		2x SDC v 3.0, 1x SD, UART, I2C, I3C, SPI, configurable GPIOs, sensor I/O to Qualcomm Sensing Hub 3.0	
• **Power/Battery**		Power management and battery charging solution on SOM	
• **Operating Environment**		Input voltage: 3.7V nominal Operating Temperature: -25°C to +85°C	
• **Form Factor**		54 x 45 x 3.61 mm LGA SOM	

Software:

• **OS Support**	Android™ 13 and Linux Yocto Kirkstone

** QCS8550 Chipset Performance, see SOM Release Notes for details on tested configurations and platforms.*



Companion Development Kit, accessories available separately

Purchasing Information:

QC-SIP-8550W-A	8GB LPDDR5x, 128GB UFS, Wi-Fi, SOM
QC-SIP-8550W-B	16GB LPDDR5x, 128GB UFS, Wi-Fi, SOM
QC-SIP-8550W-C	8GB LPDDR5x, 1TB UFS, Wi-Fi, SOM
LOQ-8550-EVK	Open-Q 8550CS SOM Development Kit

Alternate SOM configurations available by special order (minimum order quantities apply) - e.g. different memory size, etc. Contact sales to discuss your specific needs today.

Certifications

© 2026 Lantronix, Inc. All rights reserved. Lantronix is a registered trademark of Lantronix, Inc. in the U.S. and other countries. Open-Q is a trademark of Lantronix, Inc. Qualcomm and Qualcomm Dragonwing are trademarks or registered trademarks of Qualcomm Incorporated. Qualcomm QCS8550, Qualcomm Adreno, Qualcomm Hexagon, Qualcomm Kryo, Qualcomm Spectra and Qualcomm AI Engine are products of Qualcomm Technologies, Inc. and/ or its subsidiaries. Qualcomm, Adreno, Hexagon, Kryo and Spectra are trademarks of Qualcomm Incorporated, registered in the United States and other countries. All other trademarks are the property of their respective owners. Specifications subject to change without notice. Not all features listed may be supported in software. MPB-00242 Rev G (A4)

Learn more at lantronix.com/open-q-8550-som

LANTRONIX®