

# S24TXA

## Unmanaged Fast Ethernet Switch

### (24) 10/100Base-TX Ports



The S24TXA compact Fast Ethernet Switch has (24) 10/100Base-TX ports with low latency and error-free performance provided via an advanced store-and-forward architecture.

### Ordering Information

#### S24TXA

(24) 10/100Base-TX port switch "small form factor", Includes 19" Rack Mount ears

#### Power Cord Included

To order the corresponding country specific power cord, add the extension from the list below to the end of the SKU; Ex: S24TXA-NA

#### -NA = Country Code

- NA = North America
- LA = Latin America
- EU = Europe
- UK = United Kingdom
- SA = South Africa
- JP = Japan
- OZ = Australia
- BR = Brazil

### Features

- Auto-MDI/MDIX
- Wire Speed Performance
- Auto-Negotiation
- Store-and-forward Architecture
- Ruggedized metal chassis with internal power supply
- Front panel LED status indicators

### Specifications

Standards	IEEE 802.3 IEEE 802.3u IEEE 802.3x
Address Support	8K MAC address table
Latency	5 ms
Memory Buffer	1.75Mbits
Packet Forwarding	Store-and-Forward
Backplane	4.8 Gbps for S24TXA
Status LEDs	Power, Link/Activity
Dimensions	Width: 9.8" [250 mm] Depth: 5.2" [132 mm] Height: 1.5" [37 mm]
Power Supply	Universal AC power input: 100 to 240 VAC 50 – 60 Hz; Output rate: +3.3V/3A
Environment	Operating: 0°C to 45°C Storage: -40°C to 70°C Humidity: 10% to 90% (non-condensing)
Weight	3 lbs. [1.35 kg]
Compliance	Safety: UL, cUL Emissions: FCC Class A, CE Mark
Warranty	Lifetime