



Simplify Management of Your IT Equipment And Your Entire Network Infrastructure

The Secure Lantronix Management Appliance (SLM™) is a ‘master control center’ that seamlessly integrates equipment connected by console servers, KVMs, and remote power managers.

Due to the demands of modern day business, network infrastructures continue to grow along with the number of “out-of-band infrastructure” (OOBI) management devices. With Lantronix’ SLM™, ‘managing the management equipment’ is no longer a challenge. Through a centralized point of access and common interface, the SLM enables administrators to quickly and easily access equipment anywhere in the enterprise with just a few mouse clicks.

Consolidated Access and Authentication

The SLM simplifies administration by offering multiplatform client access through a standard web browser for a single point of consolidated access with simplified views to OOBI management devices and attached equipment. This centralized



SLM™ Highlights:

- Consolidate management of IT infrastructure
- Maintain a secure central point of access to all equipment
- Reduce troubleshooting and repair time
- Dynamically discover device on local or remote subnet
- Minimize total cost of ownership and administrative resources
- Maximize equipment up-time

authentication minimizes administrative burdens. Additionally, since user account information is maintained in one place, there is no need to maintain separate user-names/passwords for each management device. Users can also be remotely authenticated using LDAP, RADIUS, NIS, Kerberos and TACACS+.

Reduced Operating Costs

Streamlining overall operations reduces administration and maintenance costs. With consolidated remote access, network administrators can quickly isolate and access problem equipment. This can minimize the impact of system down time, and improve employee and company productivity. Additionally, the SLM reduces total cost of ownership for data center equipment. Automated firmware deployment tools also reduce time and labor.

Simplified and Bulletproof Security

The SLM helps IT departments adhere to corporate security policies. As a proxy between administrators and OOB management devices, access is well defined and easily controlled, particularly where access is required outside a firewall or NAT-based router. Users are only allowed to access the devices and attached equipment with granted access specific rights for read-only or read/write access, and provisions for remote authentication. To ensure accountability, user access audit logs maintain a record of login success/failure, user login/logout, and port open/close activity. And whether connecting via a web browser or a command line (CLI), 128-bit encryption (SSL/SSH) ensures secure connections to the end-user equipment along with strong authentication.

Features and Specifications

> System Capacity

- Managed Devices: 256 max.
- Users: 25 simultaneous users

> Hardware

- Processor: Intel® Pentium® 4, 3.0 GHz
- RAM: 2 GB
- Hard Disk: 250 GB
- Ethernet: Two (2) 10/100/1000Base-T (RJ45)
- Console: RS-232 (DB9)
- USB: Four (4); front (2), rear(2)

> Operating System

- Linux

> Power Requirements

- 100-240VAC, 50 to 60 Hz, 250W

> Physical

- Dimensions (HxWxD): 1U, 4.3 x 42.4 x 35.6 cm (1.7 x 16.7 x 14 in.)
- Weight: 7.7 kg (17 lbs.)
- Shipping Weight: 10.5 kg (23 lbs.)

> Environmental

- Operating: 10°C to 35°C (50°F to 95°F)
- Storage: -40°C to 70°C (-40°F to 158°F)

> Certifications

- FCC, C/UL,TUV, CE

> Warranty

- 2-year limited warranty

* RoHS-5 compliant - under the exception for Server and Network infrastructure equipment.

Advanced Feature Set

For quick and easy setup, Auto Discovery finds device and port assignment, eliminating the time-consuming task of manual configuration. Auto Discovery supports Lantronix Discovery Protocol (LDP) for SLC Console Servers and SNMP for all other devices. With the click of a button the SLC Update tool automates firmware deployment to console servers. All console messages are captured and stored to the internal hard drive, providing secure and permanent storage. Console logs may be conveniently accessed through the web interface. System configurations can also be saved and restored, providing rapid recovery of inadvertent configuration changes and peace of mind. Dual Ethernet adapters provide connection to OOB management devices on the network, while remote users connect through another, providing greater security.

Web Interface

The screenshot shows the Lantronix SLM256 web interface. The browser address bar displays <https://172.18.100.22>. The page title is "LANTRONIX SLM". Below the title, there is a search bar with "Table: Ethernet Device", "Field: Name", and "Value: sysadmin@SLM4F37". There are "Search", "Reset", and "Logout" buttons. The main content area is titled "Manage 'SLC' Group" and contains a table with columns: Name, IP Address, Ethernet Address, Device Type, Location, Model, FW Ver, Last FW Update, Login, and Cha Key. The table lists several devices, including Gary_SLC48-03, Kevins_SLC, LabSLC, MartinsSLC, misc48, slc0085, slc0b6d-Gary, Gary_SLB-02, Iyonsb, SLB0884-QN, Spider, Garys-Linux-PC-SLSA38C, Iyonspidr 76, SLS8C056E, SLSa38c0b0, SLSa38c0fb2, and SLSa38C8858. Below the table, it says "7 Items".

- Interactive web interface requires no special software.
- Authenticated users only have access to authorized devices.
- Built in SSH Web Client provides secure access.
- Console messages logged for audit and control.

Ordering Information

United States

Call: 800.422.7055

Email: sales@lantronix.com

Buy Online: <http://www.lantronix.com>

NASDAQ: LTRX

Europe

Call: +31 (0) 76.52.3.6.74 4

Email: EMEA@lantronix.com

Asia/Pacific

Call: +852 3428.2338

Email: asiapacific_sales@lantronix.com

Japan

Call: +81.3.6277.8802

Email: japan_sales@lantronix.com

> Part Number

SLM25612N-02

> Description

Secure Lantronix Management Appliance

