


Spotter

Autonomy, Swarming and Real-Time Decision Making

Powered by Qualcomm®
Dragonwing™ QCS6490
System-on-Chip



Production-Aligned Edge AI and Flight Integration for Next-Gen UxV's

Spotter is a compact, production-aligned robotics reference platform designed to accelerate the development of AI-enabled and autonomous systems across aerial, ground and maritime applications. Powered by Qualcomm® Dragonwing™ QCS6490 chipset, Spotter combines high-performance vision processing, sensor integration, vehicle-control interfaces and high-speed connectivity in a compact 40 × 120 mm form factor.

Built for real-world autonomous platforms, Spotter integrates the key interfaces required for cameras, telemetry, navigation sensors, control systems and external payloads. Dual MIPI CSI, analog video, Ethernet, USB and flexible GPIO, SPI, I²C and UART interfaces provide a versatile foundation for perception, navigation, inspection, surveillance and other edge-AI workloads.

Unlike general-purpose embedded development kits, Spotter is engineered around the requirements of mobile robotic and drone systems. Its integrated hardware and software architecture helps OEMs reduce system-integration effort, accelerate proof-of-concept development and move more efficiently toward a production-ready autonomous platform.

Key Features

- Qualcomm® Dragonwing™ QCS6490 SoC
- Up to 8GB LPDDR5 RAM + 64GB eMMC
- Up to 12.5 TOPS of AI performance
- Dual MIPI CSI camera interfaces with C-PHY / D-PHY support
- Analog / CVBS video input and output
- Qualcomm Linux for long term deployment
- Optional STM32H7-class flight / vehicle controller
- Dual IMU, compass and barometer sensor integration
- Multiple high speed connectivity options

Applications

- AI-enabled UxV platforms
- FPV drone platform modernization
- Short-range reconnaissance-class systems
- Autonomous and assisted navigation
- Vision-based detection and tracking
- RGB and thermal imaging payloads
- Multi-drone coordination and teaming
- Attributable autonomous systems
- Ground robots and unmanned ground vehicles
- Maritime surface and subsea autonomy

UxS Engineering Services:

We provide a full solution for UxS systems – our unparalleled engineering expertise and product development skills deliver innovative UxS products that are cost-effective and can jumpstart your Go-to-Market timeline.

Our business model includes turnkey product development services, or we can augment your team in specific areas of development. The choice is yours.

Specialized UxS Capabilities:

- Camera sensor integration and multi-camera systems
- Advanced image tuning for low light, high contrast, and aerial conditions
- Machine learning for autonomous navigation and object detection
- Image and video stabilization for in-flight capture
- Complex camera use-cases: multiple concurrent cameras, gimbal integration, in-camera features, sensor synchronization
- Optimized mechanical, RF, thermal, and power design for extended flight performance




Hardware Specifications:

• Processors		Qualcomm® Dragonwing™ QCS6490 SoC built on 6nm technology: Kryo™ 670 Octa-core CPU: 1 Prime @ 2.7 GHz + 3 Gold @ 2.4 GHz + 4 Silver @ 1.8 GHz Hexagon™ 770 with Hexagon Vector eXTensions (HVX)
		Adreno™ 643L GPU @ Fmax Spectra™ Spectra™ 570L ISP Adreno™ 633 video processing unit
		Adreno™ 1075 display processing unit 6th Gen Qualcomm AI Engine Secure processing unit
		MCU: Optional STM32H7: Arm® Cortex®-M7 core up to 480 MHz with DSP and double-precision FPU; 2 MB Flash + 1 MB RAM; advanced timers, PWM, ADC and high speed peripheral interfaces for real-time vehicle and flight control.
• Memory/Storage		Up to 8GB LPDDR5 and 64GB eMMC configuration (other configurations available upon request)
• Display Interfaces		Support for USB3.1 Type-C with DisplayPort v1.4 and USB 2.0 Analog Video Output
• Camera Interfaces	Digital	2x 4-lane MIPI CSI D-PHY 1.2 Spectra 570L ISP supporting 36 MP + 22 MP at 30 fps or three 22 MP at 30fps ZSL.
	Analog	CVBS / analog camera input
• Video Performance	Decode	Video decode up to 4K60. Native decode for H.265/H.265/VP9
	Encode	Video encode up to 4K30. Native encode for H.265/H.265; Support for HDR10 and HDR10+ playback
	Dec & Enc	Concurrent 1080p60 Decode and 1080p60 Encode or 4K30 Decode and 4K30 Encode
• Integrated Sensors		Dual 6-Axis IMUs — 2.8 mdps/√Hz gyro noise, 70 µg/√Hz accel noise Precision Barometer — ±0.03 hPa relative accuracy, ~±25 cm altitude 3-Axis Magnetometer — 0.3 µT/LSB resolution, up to 200 Hz output
• High Speed Connectivity		1x GBE Port 1x USB 3.1 with support for Type-C + DisplayPort v1.4 with USB SS data concurrency Addon Connectivity via USB-C for WiFi Debugging 1x PCIe Gen3 2-lane; 1x PCIe Gen3 1-lane for connectivity
• I/O Interfaces		8x PWM, MAVLink, UART, I2C, I3C, SPI, configurable GPIOs, sensor I/O to dedicated Hexagon™ sensor DSP
• RC Interface		Dedicated configurable ELRS interface
• Power Consumption		<7 Watts (typical)
• Operating Environment		Input voltage: 4.2V nominal Operating Temperature: -20°C to +85°C
• Form Factor		40x120mm with 30x30 Mounting Holes

Software:

• OS Support	Qualcomm Linux; Betaflight / PX4 /Mavlink Support
---------------------	---

* QCS6490 Chipset Performance, see SOM/SIP Release Notes for details on tested configurations and platforms.



Purchasing Information:

SKU	Description
SPTR-4WN-DL-1G	8GB LPDDR5 / 64GB eMMC w/ MCU
Alternate SOM and Board configurations available by special order (minimum order quantities apply) - e.g. different memory size, etc. Contact sales to discuss your specific needs today.	

Certifications



© 2026 Lantronix, Inc. All rights reserved. Lantronix is a registered trademark of Lantronix, Inc. in the U.S. and other countries. Open-Q is a trademark of Lantronix, Inc. Qualcomm and Qualcomm Dragonwing are trademarks or registered trademarks of Qualcomm Incorporated. Qualcomm QCS6490, Qualcomm Adreno, Qualcomm Hexagon, Qualcomm Kryo, Qualcomm Spectra and Qualcomm AI Engine are products of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm, Adreno, Hexagon, Kryo and Spectra are trademarks of Qualcomm Incorporated, registered in the United States and other countries. All other trademarks are the property of their respective owners. Specifications subject to change without notice. Not all features listed may be supported in software. MPB-00349 Rev. A

Learn more at lantronix.com/spotter